



Telephone: (01262) 603721
Facsimile: (01262) 400028
E-Mail: info@steratape.com

PRODUCT DATA

PRODUCT: 1571/F

ISSUE NUMBER: 130510/5

	<u>SUBSTANCE</u>	<u>THICKNESS</u>
Adhesive	25gsm	25 micron
Liner	65gsm	55 micron

PRODUCT DESCRIPTION

A carrier free transfer tape with an acrylic based permanent adhesive. The liner is a two sided release system which overlaps at each edge to give a 'finger-lift' product for easy liner removal.

APPLICATIONS

Used for business forms requiring an acrylic adhesive such as medical records. Especially useful for applicator fed print finishing applications where minimal adhesive build up on the cutting blade is desirable.

<u>ADHESIVE PROPERTIES</u>	<u>20 min</u>	<u>24 hour</u>	<u>TEST METHOD</u>
Adhesion to steel	300 N/M	350 N/M	BS7116:1990 - D
Shear Adhesion	100 hours		BS7116:1990 - B
Release of liner from adhesive	10 N/M		BS7116:1990 - E

THERMAL PROPERTIES

Recommended service temperature range -25°C to 120°C
Application temperature range 5°C to 50°C

SHELF LIFE

Minimum shelf life when stored in closed cartons
away from direct sources of heat and sunlight 2 Years

NOTE

Values given are average and should not be taken as a maximum or minimum for specification purposes. Specific technical details, application information & suggested uses available.

WARRANTY

All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance only. The Company is not bound contractually unless and until an order acknowledgement in writing is made and must be on the Company's standard Condition of Sales. It is recommended that the Purchasers independently determine the suitability of the products for their purposes. No salesman, representative or agent is authorised to give any guarantee, warranty or make any representation contrary to the foregoing.

SteraTape Ltd
Lancaster Road
Carnaby Ind. Est.
Bridlington
YO15 3QY
ENGLAND

Registered in England No. 2390276