



Telephone: (01262) 603721
 Facsimile: (01262) 400028
 E-Mail: info@steratape.com

PRODUCT DATA

PRODUCT: 1579/F

ISSUE NUMBER: 130510/3

	<u>SUBSTANCE</u>	<u>THICKNESS</u>
Adhesive	25gsm	25 micron
Liner	90gsm	75 micron

PRODUCT DESCRIPTION

A carrier free transfer tape with a pure acrylic permanent adhesive. The liner is a two sided release system which overlaps at each edge to give a 'finger-lift' product for easy liner removal.

APPLICATIONS

Used for sealing autoclave bags and for some print-finishing and business form applications.

<u>ADHESIVE PROPERTIES</u>	<u>20 min</u>	<u>24 hour</u>	<u>TEST METHOD</u>
Adhesion to steel	300 N/M	350 N/M	BS7116:1990 - D
Shear Adhesion	100 hours		BS7116:1990 - B
Release of liner from adhesive	10 N/M		BS7116:1990 - E

THERMAL PROPERTIES

Recommended service temperature range -25°C to 120°C
 Application temperature range 5°C to 50°C

SHELF LIFE

Minimum shelf life when stored in closed cartons
 away from direct sources of heat and sunlight 2 Years

NOTE

Values given are average and should not be taken as a maximum or minimum for specification purposes. Specific technical details, application information & suggested uses available.

WARRANTY

All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance only. The Company is not bound contractually unless and until an order acknowledgement in writing is made and must be on the Company's standard Condition of Sales. It is recommended that the Purchasers independently determine the suitability of the products for their purposes. No salesman, representative or agent is authorised to give any guarantee, warranty or make any representation contrary to the foregoing.

SteraTape Ltd
 Lancaster Road
 Carnaby Ind. Est.
 Bridlington
 YO15 3QY
 ENGLAND

Registered in England No. 2390276