



Telephone: (01262) 603721  
 Facsimile: (01262) 400028  
 E-Mail: info@steratape.com

## PRODUCT DATA

**PRODUCT: 2669**

**ISSUE NUMBER: 240707/3**

	<u>SUBSTANCE</u>		<u>THICKNESS</u>
Adhesive	55gsm		
Tissue	12gsm	Adhesive & Carrier	130 micron
Adhesive	65gsm		
Liner	120gsm	Liner	105 micron

### PRODUCT DESCRIPTION

A permanent tape with a tissue carrier. The adhesive is a high cohesion high performance modified acrylic, offering premium adhesion to a wide variety of surfaces, together with good UV light resistance, chemical resistance and performance over a wide temperature range. The line is a two sided high calliper release system.

### APPLICATIONS

A premium product especially useful in demanding mounting and nameplate applications. Also useful for splicing and foam and rubber applications. The tape has exhibited compliance to RES 30 EE 102/85 and NES MO132 Method 1 Class 5A when tested to ABS and painted steel.

<u>ADHESIVE PROPERTIES</u>		<u>20 min</u>	<u>24 hour</u>	<u>TEST METHOD</u>
Adhesion to steel	open side	600 N/M	650 N/M	BS7116:1990 - D
	closed side	600 N/M	650 N/M	BS7116:1990 - D
Shear Adhesion	open side	20 hours		BS7116:1990 - B
	closed side	20 hours		BS7116:1990 - B
Release of liner from adhesive		5 N/M		BS7116:1990 - E

### THERMAL PROPERTIES

Recommended service temperature range	-40°C to 140°C
Application temperature range	5°C to 50°C

### SHELF LIFE

Minimum shelf life when stored in closed cartons away from direct sources of heat and sunlight	2 Years
--	---------

### HEALTH AND SAFETY INFORMATION

The adhesive conforms to F&DA Regulation 175.105 and BGA regulation chapter XIV

#### NOTE

Values given are average and should not be taken as a maximum or minimum for specification purposes. Specific technical details, application information & suggested uses available.

#### WARRANTY

All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance only. The Company is not bound contractually unless and until an order acknowledgement in writing is made and must be on the Company's standard Condition of Sales. It is recommended that the Purchasers independently determine the suitability of the products for their purposes. No salesman, representative or agent is authorised to give any guarantee, warranty or make any representation contrary to the foregoing.

**SteraTape Ltd**  
 Lancaster Road  
 Carnaby Ind. Est.  
 Bridlington  
 YO15 3QY  
 ENGLAND

Registered in England No. 2390276