Telephone: (01262) 603721
Facsimile: (01262) 400028
E-Mail: info@steratape.com

P R O D U C T D A T A

PRODUCT: 4089

ISSUE NUMBER: 240707/3

	SUBSTANCE		THICKNESS
Adhesive (Open)	25gsm		
Polyester	17gsm	Adhesive & Carrier	50 micron
Adhesive (Closed)	14gsm		
Liner	120gsm	Liner	105 micron

PRODUCT DESCRIPTION

A permanent/peelable two side tape with a polyester carrier. The open side has a modified acrylic permanent adhesive and the closed side a peelable acrylic adhesive. The liner is a two side release system at high calliper facilitating removal. This product has good resistance to UV light, plasticisers and temperature variation.

APPLICATIONS

The special perm/peel feature of this tape makes 4089 ideal for protection/scratch pads, poster mounting or core splicing. The polyester carrier offers both dimensional stability and good die-cutting characteristics, ideal for foam/rubber gaskets.

ADHESIVE PROPERTIES		20 min	24 hour	TEST METHOD
Adhesion to steel	open side	600 N/M	800 N/M	BS7116:1990 - D
	closed side	150 N/M	200 N/M	BS7116:1990 - D
Shear Adhesion	open side	40 hours		BS7116:1990 - B
	closed side	2 hours		BS7116:1990 - B
Release of liner from adhesive		5 N/M		BS7116:1990 - E

THERMAL PROPERTIES

Recommended service temperature range	-25°C to 120°C
Application temperature range	5°C to 50°C

SHELF LIFE

Minimum shelf life when stored in closed cartons away from direct sources of heat and sunlight	2 Years

HEALTH & SAFETY INFORMATION

The adhesive conforms to F&DA Regulation 175.105 for indirect food contact.

NOTE

Values given are average and should not be taken as a maximum or minimum for specification purposes. Specific technical details, application information & suggested uses available.

WARRANTY

All data relating to suitable uses and description information concerning our products are compiled from research and are believed to be reliable but are provided for guidance only. The Company is not bound contractually unless and until an order acknowledgement in writing is made and must be on the Company's standard Condition of Sales. It is recommended that the Purchasers independently determine the suitability of the products for their purposes. No salesman, representative or agent is authorised to give any guarantee, warranty or make any representation contrary to the foregoing.

SteraTape Ltd
Lancaster Road
Carnaby Ind. Est.
Bridlington
YO15 3QY
ENGLAND

Registered in England No. 2390276